

vivid.

MATRIX[®] OMNI-FLOW

Matrix[®] Omni-Flow is a fully automated feeder, that is quick & easy to install, set-up and operate.



KEY FEATURES

- Retrofits to Matrix Pneumatic & Duplex Systems
- Quick & easy to set-up
- Fully automated lamination & foiling
- Change between paper stock in seconds

GREAT FOR USE IN

- Digital print shops
- Commercial printers
- Copy and print shops
- In-house print

IDEALLY SUITED FOR

- Foiling Prints
- Business cards
- Menus
- Book covers
- Brochures
- Flyers

and many more...



Enfoque Digital



▲ Omni-Flow 330 (SRA3)



▲ Omni-Flow 380 (SRA3)

Specifications	Omni-Flow 330 (SRA3)	Omni-Flow 380 (SRA3)
Max. paper Stack Height	100mm/4"	200mm/8"
Paper Thickness (gsm)	160-350	160-350
Maximum Sheet Width	330mm/13"	380mm/15"
Minimum Sheet Width	140mm/5"	125mm/4"
Maximum Sheet Length	650mm/25"	650mm/25"
Compatibility	MX-370P / MX-370DP / MX-530P / MX-530DP/ MX-370MP **	MX-370P / MX-370DP / MX-530P / MX-530DP/ MX-370MP **
Overall Dimensions WxDxH (mm/inches)	530x1000x1060mm/20x39x41"	685x1000x1160mm/26x39x45"
Weight (kg/lbs)	75/165	108/188
Power	165W (220v 50/60Hz)	2000W (220v 50/60Hz)
Warranty*	1 year	1 year

* For full terms & conditions on parts and labour warranty, visit vivid-online.com/support/warranty_information

** Maximum speed of Omni-Flow is determined by the maximum speed of the Matrix used

** Models from 2018

Vivid Laminating Technologies Ltd

+52 (55) 5393-4917

info@enfoquedi.com.mx

enfoquedi.com.mx

Oficinas CDMX / Gro.